

Gas Distribution Incidents: Understanding the Hazards

Hazards

Fires

A Presentation by

Cheryl J. Trench

Vehicles

Plumbers

Based on preliminary findings of an examination of gas distribution incidents, 1999-2003, prepared under contract to the The Cable Guy Office of Pipeline Safety

Excavation

Appliances

Allegro Energy Consulting

P.O. Box 230592 New York, NY 10023

ctrench@rcn.com

December, 2004 Washington, DC




A Fresh Look at Incident Reports, 1999-2003

- ** Old broad cause categories made it difficult to assess real hazards
 - → Damage by Outside Forces includes natural forces; excavation & mechanical damage; other outside force
 - ✓ Different hazards; different actors; different strategies
 - → "Other" = 25%; the Black Hole of Information
- * Earlier work highlighted the role of "other outside force": vehicles, fires
- ** New reporting form (early 2004) uses 7 1st-level and 25 2nd-level causes
- * Approach: use operator's narrative to re-classify from old 5 causes to new 25 2nd-level causes




Natural Gas in >60% of U.S. Homes






Mains and Services by Material, Average End-Year, 1999-2003



Average End-Year, 1999-2003
1.0 Million Miles



Average End-Year, 1999-2003 56.1 Million Services



RSPA Form 7100.1: Gas Distribution Incidents

- ***** Event that involves a release of gas and
 - → A death, or personal injury w/in-patient hospitalization,
 - → Estimated property damage, including gas lost, of \$50,000 or more
- ***** Event that results in emergency shutdown of LNG facility
- Event that is significant in the judgment of the operator, even though it did not meet other criteria



Reasons for Reporting

*** Of the 634 incidents reported, 1999-2003**


- **√** 33% involved a fatality or an injury
- **√** 48% of incidents reported for damage alone
- √ 9% of incidents reported based on operator judgment only
- √ 4% met damage threshold AND significant in view of oper.
- **√** 6% apparently not reportable
- * Retained all in analysis, even not reportable



Do Not Read Frequency of Consequence from Reportables

* Shorthand: Only reportable if something bad happens; tens of thousands of leaks repaired


each year without a reportable incident



Source: RSPA Form 7100.1 and 7100.1-1, 1999-2003



Old "Big Bucket" Causes: Similar 90-02 (AGF) and 99-03 (Allegro Energy)



AGF: Based on compilation of gas distribution incidents by American Gas Foundation (in publication)




The New Causes: Seven 1st-Level, 25 2nd-Level

- *** F1 Corrosion**
 - → 1) External; 2) Internal
- *** F2 Natural Forces**
 - → 3) Earth; 4) Lightning; 5) Rains/Floods; 6) Temperature; 7) Winds
- ***** F3 Excavation
 - → 8) Operator; 9) Third Party
- *** F4 Other Outside Force Damage**
 - → 10) Fire First; 11) Vehicle; 12) Prev. Dam'g'd Pipe; 13) Vandalism
- *** F5 Materials or Welds**
 - → Mat'l: 14)pipe, 15)component, 16)joint; Weld: 17)butt, 18)fillet, 19)seam
- *** F6 Equipment or Operations**
 - → 20) Malfunction; 21) Threads; 22) Seals; 23) Incorrect operation
- * F7 Other
 - → 24) Miscellaneous; 25) Unknown




From the Old Big Buckets to the New Big Buckets (i.e., 1st-Level Causes)






And Now, the New Small Buckets (i.e., 2nd-Level Causes): Hazards, Actors





System Part Involved





Drilling Down:

Excavation/Mechanical Damage

- * 243 incidents of 634; 38% total; 35% Third Party/4% Operator
- * Includes traditional excavation and mechanical damage
 - → Construction; sewers; road grading
 - → The cable/phone guy
 - → Also includes plumbers and others
- ** About 3/4 are activities that would require One-Call
- * Not the whole "outside force" story



Drilling Down: Fire First

- * 70 incidents of 634: 11%
- * An event where a building is on fire and the utility responds, but the fire is not a result of a gas leak.
- * A house fire that is not caused by a gas leak is arguably not a "gas incident," and it does not represent a failure of the utility to control a hazard.
- * Inconsistent reporting
 - → Over-represented in Alaska with Enstar at 25 of 70 incidents; Other companies are not reporting in this manner (next highest is 8; most, if any, are 1 or 2).
 - → This clear inconsistency undermines this category's usefulness in assessing true hazards.



Drilling Down: Vehicles

- ***** 67 incidents of 634; 11%; 25% of fatalities
- * Not a failure of gas system
- * Accidents; some DUI; some roll-aways
- * Mainly meter set assemblies (44); service lines (12); "other" system part (9)




Drilling Down:

"Miscellaneous" and Customer Piping

- *** 41 incidents of 634; ~7%**
- * About half involves customer piping and appliances: non-jurisdictional
- **☀ Varied well, "miscellaneous" causes**
- * Customer piping/appliances are 38 of total incidents; most are misc. (21) or unknown (4)




System Part by 1st-Level Cause






Fatality Incidents by Part by Cause





Injuries by Part by Cause





Summary: Diverse Hazards Will Require Diverse Strategies

- * Additional detail on causes is critical to enhancing safety
- * Many incidents not failures of gas system
- * Many incidents not on DOT-jurisdictional facilities
- * Enhancing safety will require broad partnerships of stakeholders, including
 - **→ DOT**
 - **→** Operators
 - → States
 - → Other utilities; building trades; developers; architects
 - → Homeowners and other customers